

Afmetingen op standaardbanden																	
	G1100	G1200	G1500	G1500 X-TRA (HD)	G1500L X-TRA (HD)	G2200E	G2200E X-TRA	G2300 (HD)	G2300 X-TRA (HD)	G2500 HD	G2500 X-TRA HD	G2700 HD	G2700 X-TRA HD	G2700 HD+	G2700 X-TRA HD+	G2700E	G2700E X-TRA
	Alle formaten zijn in mm aangegeven																
A	1.230	1.230	1.370	1.420	1.520	1.530	1.580	1.530	1.580	1.650	1.700	1.650	1.700	1.650	1.700	1.650	1.700
B	2.230	2.230	2.670	2.720	2.870	2.890	3.054	3.090	3.140	3.240	3.320	3.410	3.470	3.410	3.470	3.410	3.470
C	2.840	2.840	3.360	3.520	3.620	3.590	3.830	3.880	3.910	4.020	4.080	4.180	4.240	4.180	4.240	4.180	4.240
D	1.020	1.020	1.140	1.140	1.140	1.260	1.260	1.260	1.260	1.341	1.341	1.380	1.380	1.380	1.380	1.380	1.380
E	2.060	2.060	2.320	2.320	2.320	2.300	2.300	2.300	2.300	2.330	2.330	2.340	2.340	2.340	2.340	2.390	2.390
E (CAB)	-	-	-	-	-	-	-	2.280	2.280	2.350	2.350	-	-	-	-	-	-
F	1.410	1.410	1.550	1.150	1.150	1.670	1.450	1.480	1.250	1.750	1.520	1.750	1.460	1.750	1.460	1.780	1.530
G	1.380	1.380	1.830	1.360	1.360	1.990	1.680	1.988	1.680	2.150	1.760	2.210	1.750	2.210	1.750	2.210	1.750
H	2.170	2.170	2.560	2.070	2.070	2.800	2.450	2.825	2.450	2.970	2.520	2.980	2.520	2.980	2.520	2.980	2.520
I	2.980	2.980	3.140	2.640	2.640	3.390	3.040	3.390	3.040	3.530	3.090	3.570	3.100	3.570	3.100	3.570	3.100
J	43°	43°	41°	44°	44°	43°	41°	43 °	41°	43°	42°	45°	42°	45°	42°	45°	42°
K	43°	43°	52°	55°	55°	47°	46°	53°	46°	43°	47°	53°	46°	53°	46°	53°	46°
L	46°	46°	44°	41°	41°	53°	37°	47°	37°	45°	37°	37°	37°	37°	37°	37°	37°
M	34°	34°	27°	27°	27°	29°	29°	26°	26°	28°	28°	25°	25°	25°	25°	25°	25°
N	ø 570	ø 570	ø 750	ø 750	ø 750	ø 760	ø 760	ø 760	ø 760	ø 850	ø 850	ø 850	ø 850	ø 850	ø 850	ø 850	ø 850
1A	2.225	2.225	2.257	2.469	2.469	2.599	2.650	2.599	2.650	2.972	3.045	2.972	3.045	2.972	3.045	2.972	3.045
1B	1.967	1.967	1.900	2.263	2.263	2.292	2.342	2.292	2.342	2.560	2.623	2.560	2.623	2.560	2.623	2.560	2.623
1C	978	978	1.040	1.163	1.163	1.179	1.230	1.179	1.230	1.460	1.523	1.460	1.523	1.460	1.523	1.460	1.523
1D	920	920	890	1.100	1.100	1.080	1.080	1.080	1.080	1.100	1.100	1.100	1.100	1.100	1.100	1.100	1.100

Kiplast in kg, in rechte positie, zonder extra contragewichten																	
S	920	920	965	1.485	1.780	1.500	1.935	1.505	1.815	1.885	2.280	1.855	2.430	2.050	2.715	1.620	2.355
T	825	825	890	1.340	1.620	1.390	1.775	1.400	1.665	1.750	2.095	1.725	2.235	1.905	2.490	1.505	2.165
U	590	590	690	970	1.185	1.080	1.330	1.085	1.245	1.360	1.585	1.340	1.695	1.480	1.865	1.175	1.640
V	435	435	535	845	890	845	1.010	850	950	1.065	1.215	1.050	1.300	1.160	1.420	920	1.260
W	1.345	1.345	1.690	1.775	2.155	2.360	2.495	2.395	2.470	2.940	3.145	2.990	3.150	3.200	3.550	2.440	3.200
X	850	850	1.140	1.210	1.485	1.645	1.725	1.665	1.695	2.050	2.170	2.070	2.220	2.225	2.455	1.740	2.220
Y	575	575	800	855	1.055	1.175	1.230	1.185	1.205	1.465	1.540	1.475	1.600	1.590	1.750	1.260	1.585

	G2700E X-TRA HD	G3500	G3500 X-TRA	G5000	G5000 X-TRA	GS800G	GS800	GS850T	GS900	GS900E	GS950T	GS950TE	Afmetingen op standaardbanden
G2700E HD	Alle formaten zijn in mm aangegeven												
1.650	1.700	1.830	1.830	2.040	2.040	670	670	830	670	670	830	830	A
3.410	3.470	3.750	3.750	4.170	4.160	1.680	1.680	1.680	1.680	1.680	1.460	1.460	B
4.180	4.240	4.570	4.570	5.000	4.990	2.230	2.230	2.230	2.230	2.230	2.230	2.230	C
1.380	1.380	1.270	1.270	1.600	1.600	360	360	320	360	360	320	320	D
2.390	2.390	-	-	2.520	2.520	1.350	1.350	1.320	1.350	1.350	1.320	1.320	E
-	-	2.250	2.330	2.550	2.550	-	-	-	-	-	-	-	E (CAB)
1.780	1.530	1.640	1.650	1.880	1.820	1.110	1.110	1.080	1.110	1.110	1.080	1.080	F
2.210	1.750	2.450	1.800	2.550	1.920	1.480	1.480	1.450	1.480	1.480	1.450	1.450	G
2.980	2.520	3.290	2.670	3.500	2.850	2.060	2.060	2.030	2.060	2.060	2.030	2.030	H
3.570	3.100	3.930	3.330	4.250	3.600	2.380	2.380	2.350	2.380	2.380	2.350	2.350	I
45°	42°	41°	41°	45°	45°	41°	41°	41°	41°	41°	41°	41°	J
53°	46°	57°	57°	54°	43°	33°	33°	33°	33°	33°	33°	33°	K
37°	37°	43°	43°	46°	46°	36°	36°	36°	36°	36°	36°	36°	L
25°	25°	22°	22°	29°	29°	20°	20°	18°	20°	20°	18°	18°	M
ø 850	ø 850	ø 780	ø 880	ø1.050	ø1.050	ø560	ø560	-	ø560	ø560	-	-	N
2.972	3.045	3.425	3.410	3.589	3.589	-	-	-	-	-	-	-	1A
2.560	2.623	2.970	3.025	3.190	3.190	-	-	-	-	-	-	-	1B
1.460	1.523	1.525	1.590	1.745	1.745	-	-	-	-	-	-	-	1C
1.100	1.100	1.340	1.340	1.460	1.460	1.100	1.100	900	1.100	1.100	900	900	1D

Kiplast in kg, in rechte positie, zonder extra contragewichten													
2.380	2.085	2.875	3.260	3.920	4.375	444	444	1.043	444	595	1.043	1.030	S
2.230	1.915	2.700	3.020	3.680	4.080	404	404	970	404	525	970	880	T
1.735	1.450	2.160	2.325	2.965	3.220	245	245	525	245	355	525	560	U
1.350	1.115	1.725	1.810	2.380	2.550	178	178	360	178	250	360	380	V
2.890	2.835	4.385	4.650	5.000	5.000	858	858	2.267	858	895	2.267	2.000	W
1.825	1.970	3.200	3.250	4.245	4.390	395	395	736	395	500	736	890	X
1.460	1.405	2.360	2.335	3.170	3.240	256	256	439	256	320	439	520	Y

